


A maximum fastening thickness



# SNK



## WHITE COUNTERSUNK HEAD SCREW FOR WOOD

- Approved universal screw for various structural applications, from small construction to timber buildings
- Certified for use on CLT and high density woods such as LVL
- Excellent tensile and yield strength of steel. Very high torsional strength for secure screwing



Data sheet available online



d <sub>1</sub> [mm] [in]	d <sub>k</sub> [mm] [in]	CODE	L		b		A		pcs
			[mm]	[in]	[mm]	[in]	[mm]	[in]	
3,5 0.14 TX 15	7,00 0.276	SNK3540	40	1 9/16	18	11/16	22	7/8	500
		SNK3550	50	1 15/16	24	15/16	26	1 1/32	400
4 0.16 TX 20	8,00 0.315	SNK440	40	1 9/16	24	15/16	16	5/8	500
		SNK445	45	1 3/4	30	1 3/16	15	9/16	400
		SNK450	50	1 15/16	30	1 3/16	20	13/16	400
		SNK460	60	2 3/8	35	1 3/8	25	1	200
		SNK470	70	2 3/4	40	1 9/16	30	1 3/16	200
4,5 0.18 TX 20	9,00 0.354	SNK4540	40	1 9/16	24	15/16	16	5/8	400
		SNK4545	45	1 3/4	30	1 3/16	15	9/16	400
		SNK4550	50	1 15/16	30	1 3/16	20	13/16	200
		SNK4560	60	2 3/8	35	1 3/8	25	1	200
		SNK4570	70	2 3/4	40	1 9/16	30	1 3/16	200
5 0.20 TX 25	10,00 0.40	SNK4580	80	3 1/8	40	1 9/16	40	1 9/16	200
		SNK550	50	1 15/16	24	15/16	26	1 1/32	200
		SNK560	60	2 3/8	30	1 3/16	30	1 3/16	200
		SNK570	70	2 3/4	35	1 3/8	35	1 3/8	100
		SNK580	80	3 1/8	40	1 9/16	40	1 9/16	100
		SNK590	90	3 1/2	45	1 3/4	45	1 3/4	100
		SNK5100	100	4	50	1 15/16	50	1 15/16	100
6 0.24 TX 30	12,00 0.472	SNK5120	120	4 3/4	60	2 3/8	60	2 3/8	100
		SNK660	60	2 3/8	30	1 3/16	30	1 3/16	100
		SNK670	70	2 3/4	40	1 9/16	30	1 3/16	100
		SNK680	80	3 1/8	40	1 9/16	40	1 9/16	100
		SNK690	90	3 1/2	50	1 15/16	40	1 9/16	100
		SNK6100	100	4	50	1 15/16	50	1 15/16	100
		SNK6120	120	4 3/4	60	2 3/8	60	2 3/8	100
SNK6140	140	5 1/2	75	2 15/16	65	2 9/16	100		
SNK6160	160	6 1/4	75	2 15/16	85	3 3/8	100		

d <sub>1</sub> [mm] [in]	d <sub>K</sub> [mm] [in]	CODE	L		b		A		pcs
			[mm]	[in]	[mm]	[in]	[mm]	[in]	
6 0.24 TX 30	12,00 0.472	SNK6180	180	7 1/8	75	2 15/16	105	4 1/8	100
		SNK6200	200	8	75	2 15/16	125	4 15/16	100
		SNK6220	220	8 5/8	75	2 15/16	145	5 11/16	100
		SNK6240	240	9 1/2	75	2 15/16	165	6 1/2	100
		SNK6260	260	10 1/4	75	2 15/16	185	7 1/4	100
		SNK6280	280	11	75	2 15/16	205	8 1/16	100
		SNK6300	300	11 3/4	75	2 15/16	225	8 7/8	100
8 0.32 TX 40	14,50 0.571	SNK880	80	3 1/8	52	2 1/16	28	1 1/8	100
		SNK8100	100	4	52	2 1/16	48	1 7/8	100
		SNK8120	120	4 3/4	60	2 3/8	60	2 3/8	100
		SNK8140	140	5 1/2	60	2 3/8	80	3 1/8	100
		SNK8160	160	6 1/4	80	3 1/8	80	3 1/8	100
		SNK8180	180	7 1/8	80	3 1/8	100	4	100
		SNK8200	200	8	80	3 1/8	120	4 3/4	100
		SNK8220	220	8 5/8	80	3 1/8	140	5 1/2	100
		SNK8240	240	9 1/2	80	3 1/8	160	6 1/4	100
		SNK8260	260	10 1/4	80	3 1/8	180	7 1/8	100
		SNK8280	280	11	80	3 1/8	200	8	100
		SNK8300	300	11 3/4	100	4	200	8	100
		SNK8320	320	12 5/8	100	4	220	8 5/8	100
		SNK8340	340	13 3/8	100	4	240	9 1/2	100
		SNK8360	360	14 1/4	100	4	260	10 1/4	100
SNK8380	380	15	100	4	280	11	100		
SNK8400	400	15 3/4	100	4	300	11 3/4	100		
10 0.40 TX 40	18,25 0.719	SNK10100	100	4	52	2 1/16	48	1 7/8	50
		SNK10120	120	4 3/4	60	2 3/8	60	2 3/8	50
		SNK10140	140	5 1/2	60	2 3/8	80	3 1/8	50
		SNK10160	160	6 1/4	80	3 1/8	80	3 1/8	50
		SNK10180	180	7 1/8	80	3 1/8	100	4	50
		SNK10200	200	8	80	3 1/8	120	4 3/4	50
		SNK10220	220	8 5/8	80	3 1/8	140	5 1/2	50
		SNK10240	240	9 1/2	80	3 1/8	160	6 1/4	50
		SNK10260	260	10 1/4	80	3 1/8	180	7 1/8	50
		SNK10280	280	11	80	3 1/8	200	8	50
		SNK10300	300	11 3/4	100	4	200	8	50
		SNK10320	320	12 5/8	100	4	220	8 5/8	50
		SNK10340	340	13 3/8	100	4	240	9 1/2	50
		SNK10360	360	14 1/4	100	4	260	10 1/4	50
SNK10380	380	15	100	4	280	11	50		
SNK10400	400	15 3/4	100	4	300	11 3/4	50		



**SHT**  
TURNED WASHER

d <sub>1 SNK</sub> [mm] [in]	CODE	D <sub>2</sub>		h		pcs
		[mm]	[in]	[mm]	[in]	
6 0.24	SHT6	20	0.787	4,5	0.177	100
8 0.32	SHT8	25	0.984	5,5	0.217	50
10 0.40	SHT10	30	1.181	6,5	0.256	50

RELATED PRODUCTS



**CAPS**

page 270



**CATCH**  
SCREWING  
DEVICE

page 263



**LEWIS BITS**  
TWIST DRILL BITS FOR  
SOFT WOOD

page 282



**SNAIL BITS**  
TWIST DRILL BITS FOR  
HARDWOOD

page 283